

Tech-Spec Sheet

Product No. MW50, MW100

Material Winches

Rev. no.:
Date:
Page:



Product Description:

The MW Series winches offer raising and lowering capabilities with a friction brake that prevents the unit from free-wheeling when under a load. Manufactured of a rugged steel frame and drum, the unit includes a #45 pulley, and a carabiner for attaching the line to an anchor point such as a tripod. Order the MW unit by choosing the preferred length and type of line:

MW50G - 50' galvanized wire rope

MW50SS - 50' stainless steel wire rope

MW50T - 50' Technora® synthetic rope

MW100G - 100' galvanized wire rope

MW100SS - 100' stainless steel wire rope

MW100T - 100' Technora® synthetic rope

The MW Series units come equipped with a bracket to fit FrenchCreek's TP7 Tripod, TP9 Tripod, FCPD300 Davit System, and the FCPQ200 Quad Pod System.

Specifications:

Housing: Plated Steel

Drive Gear: Plated Steel

Non-Drive Gear: Plated Steel

Ratio: 5.1:1

Capacity:

Materials: 500lbs

Personnel: 350lbs

Rope:

MW50G, MW100G: Galvanized 3/16 wire rope

MW50SS, MW100SS: Stainless Steel 3/16 rope

MW50T, MW100T: Technora® Synthetic Rope

#45 Split Pulley:

2 3/8" aluminum sheave, bushing, with stainless steel axle

Rope Capacity: 5/8" Size 4.25x3.25 in.

Weight: .45 lb.

354-2 Auto-locking Carabiner:

1" gate opening

Cold formed zinc chromate plated

100% proof loaded to 3600 lbs

minimal tensile: 5,000 lbs

49 Swivel Locking Snap Hook:

3/4" gate opening

Cold formed zinc chromate plated

100% proof loaded to 3600 lbs

minimal tensile: 5,000 lbs

Applicable Standards:

OSHA Subpart M 1926.502, 1910.66

ANSI A10-14, Z359.1-2007